

## TECHNICAL SHEET



## SEAGUARD FLEX

Boat equipment

CHARACTERISTICS	VALUES		UNITS	STANDARDS
	WARP	WEFT		

## OVERALL CHARACTERISTICS

Composition	Hight tenacity polyester 280 dtex coated on both sides			
Finish	Top coat soft touch - underside protective varnish			
Weight	300		g/m <sup>2</sup>	ISO 2286-1
Width	150 et 300		cm	EN 1773

## FABRIC STRENGTH

Tensile strength	110	110	daN	ISO 13934-1
Tear strength	9	9	daN	ISO 13937-1
Schmerber	> 10 000		mm	ISO 811

## COLOUR RESISTANCE

Colour fastness UV	7-8		class /8	ISO 105 B02
--------------------	-----	--	----------	-------------

## USE

Roll length	60 (300 cm)et 30 (150 cm)	Im	
Recommended use	winter cover, winch cover, protected fitted cover		
Guarantee	5	Years	

The values of this product may vary depending on a tolerance variation of +/-5%.



**Dickson - Constant SAS au capital de 12 640 000 Euros - 381 347 970 RCS Lille Métropole**  
 10, rue des Châteaux - BP 109 - Z.I la Pilaterie 59443 Wasquehal cedex - France  
 Tél. : +33.(0)3.20.45.59.59 - Fax : +33.(0)3.20.45.59.00 - [www.dickson-constant.com](http://www.dickson-constant.com)