

# BASIC INJECTION.

## MATERIAL INFORMATION

### Material:

Polypropylene resin with glass fiber.

### Process:

Injection moulding.

### Features:

Outdoor suitable.

Shock resistant.

Light weight.

100% recyclable.

### UV certificates:

Xenón UNE EN ISO 4892-2:2006

UNE CEN/TR 581-4:05 IN

### Fire Proof Certificates:

UNE EN 1021-1:15

UNE EN 1021-2:15

IMO (Maritime Fire Safety Standards)

UNI 9175:2010

BS 5852:06

### Colour references.

#### White



**PANTONE** -  
**RAL** K7 9016  
**CMYK** - 18 - 0 - 22 - 0  
**RGB** - 241 - 240 - 234

#### Black



**PANTONE** BLACK 3C  
**RAL** K7 9004  
**CMYK** 63 - 60 - 64 - 65  
**RGB** 33 - 39 - 33

#### Gris



**PANTONE** COOL GRAY 11C  
**RAL** D2 000 35 00  
**CMYK** 48 - 29 - 22 - 46  
**RGB** 84 - 88 - 89

#### Ecru



**PANTONE** 400C  
**RAL** D2 - 070 70 10  
**CMYK** 20 - 17 - 19 - 0  
**RGB** 196 - 191 - 182

#### Tortora



**PANTONE** 403C  
**RAL** D2 080 50 05  
**CMYK** 18 - 21 - 27 - 47  
**RGB** 140 - 133 - 123

#### Bronze



**PANTONE** 7589C  
**RAL** K7 - 8017  
**CMYK** 38 - 57 - 67 - 53  
**RGB** 92 - 71 - 56

#### Navy




**PANTONE** 540C  
**RAL** D2 270 30 20  
**CMYK** 100 - 53 - 0 - 65  
**RGB** 0 - 48 - 87

#### Pickle



**PANTONE** 2407C  
**RAL** D2 130 50 20  
**CMYK** 66 - 29 - 65 - 3  
**RGB** 107 - 141 - 115

#### Almond



**PANTONE** -  
**RAL** D2 130 80 20  
**CMYK** 18 - 0 - 22 - 0  
**RGB** 223 - 235 - 213

#### Mostaza



**PANTONE** 7509C  
**RAL** D2 075 70 50  
**CMYK** 4 - 29 - 57 - 4  
**RGB** 214 - 164 - 97

#### Melon



**PANTONE** 7591C  
**RAL** -  
**CMYK** 12 - 63 - 72 - 0  
**RGB** 192 - 125 - 89

#### Red



**PANTONE** 187C  
**RAL** D2 3001  
**CMYK** 8 - 100 - 70 - 33  
**RGB** 166 - 25 - 46

VONDOM